### Title 15

## **ZONING CODE**

Division IV. Citywide Development Standards, Regulations and Incentives

15.400 Dimensional Standards and Regulations

# **Chapter 15.400**

## **Dimensional Standards and Regulations**

**Sections:** 

15.400.200 Commercial, Industrial, Park Standards Chart

# 15.400.200 Commercial, Industrial, Park Standards Chart

	ZONES			ADDITIONAL REGULATIONS							
DEVELOPMENT STANDARDS	NB <u>CL</u>	<u>NVM</u>	<del>O/C/MU</del> <u>UVM</u>	<u>NVH</u>	<del>O/CM</del> <u>UVH</u> (1)	RBX (1)	СВ	CB-C (1)	I	P	(1) See Chapter 15.515 SMC for additional development standards for the RBX, URH-MU, CB-C, NVM, NVH, -and UVH zones.
MINIMUM LOT AREA	N/A	<u>N/A</u>	N/A	<u>N/A</u>	N/A	N/A	N/A	N/A	N/A	N/A	
MINIMUM AREA – DEVELOPMENT SITE	N/A	N/A	N/A	<u>N/A</u>	N/A	N/A	N/A	N/A	N/A	N/A	
MINIMUM LOT WIDTH	N/A	<u>N/A</u>	N/A	<u>N/A</u>	N/A	N/A	N/A	N/A	N/A	N/A	
MINIMUM FRONT YARD SETBACK	10'	0'	0'(1)	0'	0'	N/A	10'	0'	10'	N/A	Setback dimensions may change subject to landscape requirements. See SMC 15.445.010(C) in the landscaping chapter for applicable standards.  (1) Ten-foot setback if adjacent to a UL-RL zone.
MAXIMUM FRONT YARD SETBACK	N/A	10'_ (1)(4)	10'(1)	10'_ (1)(4)	10' (1)(4)	N/A	(5)	10' (1)(2)(3)(4)	N/A	N/A	Setback dimensions may change subject to landscape requirements. See SMC 15.445.010(C) in the landscaping chapter for applicable standards.

	ZONES			ADDITIONAL REGULATIONS							
DEVELOPMENT STANDARDS	NB <u>CL</u>	<u>NVM</u>	<del>O/C/MU</del> _ <u>UVM</u>	<u>NVH</u>	<del>O/CM</del> <u>UVH</u> (1)	RBX (1)	СВ	CB-C (1)	I	P	(1) See Chapter 15.515 SMC for additional development standards for the RBX, <u>URH-MU</u> , CB-C, <u>NVM</u> , <u>NVH</u> , –and <u>UVH</u> zones.
											(1) Within the City Center Overlay District, maximum setback is 20 feet adjacent to International Blvd. Ten feet adjacent to all other streets. See SMC 15.300.210 for additional standards.  (2) Within the S. 154th St. Station Area Overlay District, see SMC 15.305.210 for setback standards.  (3) Within the Angle Lake Station Area Overlay District, see SMC 15.310.210 for setback standards.  (4) Within the NVM, NVH, UVM, O/CMUVH and CB-C zones outside of the overlay districts, maximum setback is 20 feet for multi-family and residential mixed use projects. See SMC 15.515.200 for additional standards and maximum setback waiver requirements.

	ZONES				ADDITIONAL REGULATIONS						
DEVELOPMENT STANDARDS	NB <u>CL</u>	<u>NVM</u>	<del>O/C/MU</del> _ <u>UVM</u>	<u>NVH</u>	<del>O/CM</del> <u>UVH</u> (1)	RBX (1)	СВ	CB-C (1)	I	P	(1) See Chapter 15.515 SMC for additional development standards for the RBX, <u>URH-MU</u> , CB-C, <u>NVM</u> , <u>NVH</u> , –and <u>UVH</u> zones.
											(5) Maximum setback is 20 feet for multi-family and residential mixed use projects.
MINIMUM SIDE YARD SETBACK	5'	<u>5'</u>	5'	<u>5'</u>	5'	N/A	N/A	N/A	5'	10'	Setback dimensions may change subject to landscape requirements. See SMC <u>15.445.010(C)</u> in the landscaping chapter for applicable standards.
MINIMUM REAR YARD SETBACK	5'	5'	5'	<u>5'</u>	5'	N/A	N/A	N/A	5'	10'	Setback dimensions may change subject to landscape requirements. See SMC <u>15.445.010(C)</u> in the landscaping chapter for applicable standards.
MAXIMUM BUILDING LOT COVERAGE	65%	<u>75%</u>	<del>65%</del> 75%	<u>75%</u>	75%	75%, 85%	75%	75%	85%	N/A	See Residential/Commercial Density Incentives (Chapter 15.425 SMC).
MAXIMUM IMPERVIOUS SURFACE	N/A	<u>N/A</u>	N/A	<u>N/A</u>	N/A	N/A	N/A	N/A	N/A	N/A	

	ZONES			ADDITIONAL REGULATIONS							
DEVELOPMENT STANDARDS	NB <u>CL</u>	NVM	<del>O/C/MU</del> _ <u>UVM</u>	NVH	<del>O/CM</del> <u>UVH</u> (1)	RBX (1)	СВ	CB-C (1)	I	P	(1) See Chapter 15.515 SMC for additional development standards for the RBX, <u>URH-MU</u> , CB-C, <u>NVM</u> , <u>NVH</u> , –and <u>UVH</u> zones.
MAXIMUM STRUCTURE HEIGHT	35'	4 stories (45') (1)	5 stories (45'55') (1)	5 stories (55') (1)	6_stories_(6545')_(1)	(2+)	(21)	(24)	75'	N/A	(1) See Residential Incentives (Chapter 15.425 SMC) for additional height incentives. (2+) Limited by FAA and Fire Department regulations.